Contatti REO Italia:
+39 030 279 3883 •
info@reoitalia.it

REOTRON SMP-KMB

Installation on mounting wall



Unique Selling Point

- Very good cos PHI of 0,95
- Power Factor Correction
- Compact dimensions
- Series or parallel connection
- Air or water cooled
- Many options of combinations for different requirements with other
- REO product ranges

Description

The REOTRON SMP power supplies are primary switched power supplies with galvanic separation from the input to the output. They can be used as voltage, current or power regulators.

Operation
The unit can be operated from an internal display, external control signals of 0...+10V, 0(4)... 20mA or optionally by a fieldbus interface such as DeviceNet, ProfiBus, CanBus, EtherCAT, EtherNet/IP and ProfiNet protocols.

Input devices
The device input is designed for connection to a three-phase mains 3 x 400 V, 50/60 Hz. The compliance of EMC standards is guaranteed by an input-sided PFC-mains filter.

Design
The devices have a compact design in a 19 inch rackmount chassis and can be delivered as a installation ready control cabinet version or as a tabletop unit (lab version). The devices are air- or water-cooled.

Connection
The SMP's are connected via screw terminals and with cooper terminal buses at high output currents. Like all REO-products, the REOTRON SMP's are also available as customized versions.

High range of performance
The units can be combined to power supplies with higher ratings by connecting the units in series or parallel.

Technical Data

- Output voltage : 20 - 80 V
- Output Current : 10 - 50 A
- Output power : 200 - 1600 W
- Input voltage switchable : Eingangsspannung umschaltbar [V] V

Last modified: 26.06.2018. All data is provided to the best of our knowledge and awareness and is subject to error and amendment.

Contatti REO Italia:
+39 030 279 3883 •
info@reoitalia.it

REOTRON SMP-KMB

Installation on mounting wall

Technical Data

Type	REOTRON SMP-KMB
Input voltage:	230 V, +/- 10 %, 50/60 Hz
Ripple p-p:	100 mV/200 mV
Setpoint Input:	0...+10 V, DC 0(4)...20 mA, Potentiometer 10 kOhm internal control over display
Actual Output:	0...+10 V, DC 0(4)...20 mA, internal control over display
Interfaces (optional)	DeviceNet, ProfiBus, CanBus, EtherCAT, EtherNet/IP, ProfiNet
Control accuracy:	1% of the nominal value (higher on request)
Rating:	24 V, DC or contact
Protection:	Cabinet installation IP 20
2 x relay status:	Changer 250 V, 1A
Efficiency:	> 85 %
Cos Φ:	0,95
PFC:	0,94
Operating temperature:	0...+45 °C
Standards:	EN 50178, EN 61000-6-2, EN 61000-6-4

Last modified: 26.06.2018. All data is provided to the best of our knowledge and awareness and is subject to error and amendment.

Contatti REO Italia:
+39 030 279 3883 •
info@reoitalia.it

REOTRON SMP-KMB

Installation on mounting wall

REO Baureihe SMP-	KMB 10-10	KMB 10-20	KMB 10-30	KMB 10-40
Output power [W]	0...100	0...200	0...300	0...400
Output voltage [V]	0...10	0...10	0...10	0...10
Output current [A]	0...10	0...20	0...30	0...40
Dimensions [BxHxT]	154x330x217,5	154x330x217,5	154x330x217,5	154x330x217,5

REO Baureihe SMP-	KMB 20-10	KMB 20-20	KMB 20-30	KMB 20-40
Output power [W]	0...200	0...400	0...600	0...800
Output voltage [V]	0...20	0...20	0...20	0...20
Output current [A]	0...10	0...20	0...30	0...40
Dimensions [BxHxT]	154x330x217,5	154x330x217,5	154x330x217,5	154x330x217,5

REO Baureihe SMP-	KMB 30-10	KMB 30-20	KMB 30-30	KMB 30-40	KMB 40-10	KMB 40-20
Output power [W]	0...300	0...600	0...900	0...1200	0...400	0...800
Output voltage [V]	0...30	0...30	0...30	0...30	0...40	0...40
Output current [A]	0...10	0...20	0...30	0...40	0...10	0...20
Dimensions [BxHxT]	154x330x217,5	154x330x217,5	154x330x217,5	154x330x217,5	154x330x217,5	154x330x217,5

REO Baureihe SMP-	KMB 50-10	KMB 50-20	KMB 60-10
Output power [W]	0...500	0...1000	0...600
Output voltage [V]	0...50	0...50	0...60
Output current [A]	0...10	0...20	0...10
Dimensions [BxHxT]	154x330x217,5	154x330x217,5	154x330x217,5

Last modified: 26.06.2018. All data is provided to the best of our knowledge and awareness and is subject to error and amendment.

Contatti REO Italia:
+39 030 279 3883 •
info@reoitalia.it

REOTRON SMP-KMB

Installation on mounting wall

Dimension drawing



Last modified: 26.06.2018. All data is provided to the best of our knowledge and awareness and is subject to error and amendment.