Contatti REO Italia:
+39 030 279 3883 •
info@reoitalia.it

REOVIB MTS 442

IP 54, Two-channel control



Unique Selling Point

- Phase-angle control with programmable functions
- Two-channe control for the optimal control of the complete conveyor system
- Automatic mains voltage adjustment
- Material flow control
- Various sensor logic functions can be set
- Adjustable soft start
- With fill level/overflow control
- Integrated mains voltage compensation with constant vibration amplitude

Description

The REOVIB MTS 442 control device has two power outputs that can be linked according to the the application requirements (e.g. bowl and linear conveyors). All parameters can be input via a display integrated into the faceplate. Connections with other equipment in the REOVIB MTS series can be implemented quickly and easily. Application-specific settings can be stored and retrieved when required.

The equipment is available in a standalone IP54 housing with various connection options:
- Input cable/output socket
- Complete cable connection solution for mains, output and control connections

Typical applications

- Conveyor & assembly automation
- Conveyor technology
- Sieving technology
- Filling & packaging technology

Technical Data

- Output voltage : 20 - 100 / 40 - 210 V
- Output Current : 10 A
- Input voltage auto detect : 110 - 230 V

Last modified: 09.07.2020. All data is provided to the best of our knowledge and awareness and is subject to error and amendment.

Contatti REO Italia:
+39 030 279 3883 •
info@reoitalia.it

REOVIB MTS 442

IP 54, Two-channel control

Technical data

Mains input	110 / 230V Auto Detect
Mains frequency	50 / 60 Hz +/- 3 Hz
Output voltage	20...100 V / 40...210 V
Output current	Per output max. 6 A
Number of outputs	2
Max. Output current from all outputs	10 A
Vibration frequency	50 / 100 Hz (60 / 120 Hz)
Setpoint value	Display
Statussignal	24 V DC
Ext. Enable	24 V DC, Switch
Sensor supply	24 V DC
Setting Umin / Umax	Display
Soft start	Adjustable 0...5 sec.
With fill level/overflow control	Per output PNP, 24 V DC
Mains voltage compensation	x
Coarse/fine control	x
Selectable timer function	x
Sensor time out monitor	x
Standards Conformity	CE, RoHS
Protection class	IP54

Last modified: 09.07.2020. All data is provided to the best of our knowledge and awareness and is subject to error and amendment.

Contatti REO Italia:
+39 030 279 3883 •
info@reoitalia.it

REOVIB MTS 442

IP 54, Two-channel control

Dimension drawing



Example for complete cable connection

Last modified: 09.07.2020. All data is provided to the best of our knowledge and awareness and is subject to error and amendment.